

Cesab P0

spec sheet

Cesab P013iB

Cesab P015i

Cesab P016i



Cesab P0 Truck Specifications

IDENTIFICATION						
1.2	Model			P013iB	P015i	P016i
1.3	Drive			Electric	Electric	Electric
1.4	Operator type			Pedestrian	Pedestrian	Pedestrian
1.5	Load capacity/rated load	Q	kg	1300	1500	1600
1.6	Load centre	c	mm	600	600	600
1.8	Load distance, center of drive axle to fork (forks raised/lowered)	x	mm	884/947	884/947	887/951
1.9	Wheelbase (forks raised/lowered)	y	mm	1138/1187	1138/1187	1140/1189

WEIGHT						
2.1	Service weight including battery		kg	125	132	145
2.2	Axle load, with load, drive/castor/fork wheel		kg	550/875	565/50/1017	575/50/1120
2.3	Axle load, without load, drive/castor/fork wheel		kg	96/29	88/14/30	94/16/35

WHEELS						
3.1	Drive/castor/fork wheel			Polyurethane	Polyurethane	Polyurethane
3.2	Wheel size, front	Ø x width	mm	Ø 210×75	Ø 210×75	Ø 210×75
3.3	Wheel size, rear	Ø x width	mm	Ø 80×93	Ø 80×70	Ø 80×70
3.4	Additional wheels, dimensions	Ø x width	mm	-	Ø 80×30	Ø 80×30
3.5	Wheels, number front/rear (x = driven wheels)			1x/ 2	1x +2/ 4	1x +2/ 4
3.6	Track width, front	b ₁₀	mm	-	430	430
3.7	Track width, rear	b ₁₁	mm	380	380	380

DIMENSIONS						
4.4	Lift	h ₃	mm	115	115	115
	Lift height	h ₂₃	mm	195	195	195
4.9	Height of tiller in drive position, min./max.	h ₁₄	mm	700/1160	700/1160	700/1160
4.15	Height, fork lowered	h ₁₃	mm	80	80	80
4.19	Overall length	l ₁	mm	1537	1537	1543
4.20	Length to face of forks	l ₂	mm	388	388	394
4.21	Overall width	b ₁	mm	540	540	540
4.22	Fork dimensions	s/e/l	mm	50/160/1150	50/160/1150	50/160/1150
4.25	Width over forks	b ₅	mm	540	540	540
4.32	Ground clearance, centre of wheelbase	m ₂	mm	30	30	30
4.34.1	Aisle width for pallets 1000x1200 crossways	A _{st}	mm	2013	2013	2019
4.34.2	Aisle width for pallets 800x1200 lengthways	A _{st}	mm	2140	2140	2146
4.35	Turning radius (forks raised)	Wa	mm	1336	1336	1342

PERFORMANCE						
5.1	Travel speed, with/without load	km/h	4,6/4,8	4,6/4,8	4,8/5,2	
5.2	Lift speed, with/without load	m/s	0,020/0,025	0,020/0,025	0,017/0,022	
5.3	Lowering speed, with/without load	m/s	0,05/0,04	Ø 0,05/0,04	0,05/0,03	
5.8	Max. gradeability, with/without load	%	6/16	6/16	10/16	
5.10	Service brake		Electromagnetic	Electromagnetic	Electromagnetic	

ELECTRIC MOTOR						
6.1	Drive motor rating S2 60 min	kW	0,65	0,65	1,0	
6.2	Lift motor rating at S3 10%	kW	0,5	0,5	0,8	
6.4	Battery voltage/nominal capacity K5	V/Ah	24/20	24/40	48/20	
6.5	Battery weight	kg	5,8	8,5	8,5	
6.6	Energy consumption acc. to EN16796	kWh/h	0,17	0,18	0,20	

OTHER						
8.1	Type of drive control		DC-speed control	DC-speed control	DC-speed control	
8.4	Sound level at the driver's ear according to EN12053	dB (A)	<70	<70	<70	

