

Electric towing tractor *Tracto*

R-series
TTE40



Electric towing tractor 4.0 ton

IDENTIFICATION

1.1	Manufacturer			CESAB
1.2	Model			TTE40
1.3	Drive			Electric
1.4	Operator type			Sit-on
1.5	Load capacity/rated load	Q	kg	4000
1.7	Rated drawbar pull	F	N	1000
1.9	Wheelbase	y	mm	1000

WEIGHT

2.1	Service weight		kg	710
2.2	Axle load, with load, front/rear		kg	320 / 470
2.3	Axle load, without load, front/rear		kg	290 / 420

WHEELS

3.1	Tyre - Cushion(Cu), Extra-elastic(SE), Pneumatic(Pn),Polyurethane			SE/Pn
3.2	Wheel size, front			15x4,5-8
3.3	Wheel size, rear			15x4,5-8
3.5	Wheels, number front/rear (x = driven wheels)			1/2x
3.6	Track width, front	b ₁₀	mm	—
3.7	Track width, rear	b ₁₁	mm	818

DIMENSIONS

4.7	Height of cab	h ₆	mm	1770
4.8	Seat height	h ₇	mm	743
4.12	Coupling height	h ₁₀	mm	290 - 345 - 400
4.13	Loading height, unloaded	h ₁₁	mm	—
4.16	Length of loading surface	l ₃	mm	—
4.17	Overhang	l ₅	mm	210
4.18	Width of loading surface	b ₉	mm	—
4.19	Overall length	l ₁	mm	1520
4.21	Overall width	b ₁	mm	950
4.32	Ground clearance, centre of wheelbase	m ₂	mm	137
4.35	Turning radius	W _a	mm	1528
4.36	Internal turning radius	b ₁₃	mm	470

PERFORMANCE DATA

5.1	Travel speed, with/without load	km/h	7 / 15
5.6	Max. drawbar pull	N	3200
5.7	Gradeability	%	See chart
5.8	Max. gradeability loaded/unloaded	%	See chart
5.10	Service / parking brake (I=Hydraulic E=Electromagnetic M=Mechanical)		I / E
5.10.1	Type of service brake front/rear		— / drum

ELECTRIC MOTOR

6.1	Drive motor rating S2 60 min	kW	2
6.3	Battery according to DIN 43531 / 35 / 36 A, B, C, no		no
6.4	Battery voltage, nominal capacity ¹⁾	K ₅	V/Ah 24/240 - 300 - 360
6.5	Battery weight	kg	300 - 320 - 340
6.6	Energy consumption according to EN 16796	kWh/h	1,44

OTHERS

8.1	Electronics control		Inverter AC
8.4	Sound level at driver's ear according to EN 12053	dB(A)	69

1) Performances and weight are intended with 300 Ah battery.

As per VDI guidelines 2198, this datasheet applies to standard electric tractor / platform truck only.

Dimensions are not binding and can be changed in any moment. The performances must be intended for brand new machines, after having completed the running-in tested in CESAB factory in normal climatic conditions.

Performances and weight are to be intended with standard motors and battery and with pneumatic tires.

Some data can vary according to different equipments.

Towed weight

EXAMPLE OF GRAPH READING:







TOWED LOAD = 0,5 t

GRADIENT (i) = 5 %

DRAWBALL PUL (F) = 950 N


SPEED (V0) = 7 km/h

MAX. PRACTICABLE RAMP LENGTH (s) = 7,5 km



Standard equipments

- Operator presence system
- AC power system
- Pneumatic tyres
- Rear drawbar
- Automatic parking brake
- Regenerative braking
- Head and tail lights, turn signal lights
- Digital display



CMHE-CESAB MATERIAL HANDLING EUROPE - Version 1, 06-03-2025